

Brain Tumor Detection Using Deep Learning

Sinchana S
CSE,M.Tech Student
sinchanasinch456@gmail.com
9513866017

Dr.Girish L
Associate Professor
Department of AI & DS, SIET
Tumkur
girishltumkur@gmail.com
8970429399

Abstract

The Using medical imaging to segment brain tumors is a particularly challenging but crucial process. This is because of the potential for erroneous prognosis and diagnosis as a result of manual classification. Working with vast volumes of data also requires a lot of work. Because of their similar appearances and wide range of traits, It might be difficult to tell a brain tumor originating from healthy tissue in photographs. In this study, fuzzy C-Means was used to remove brain tumors from two-dimensional MRI images. CNN and classical classifiers were then used. The study's dataset included tumors of various sizes, shapes, and intensities. KNN, MLP, LR, SVM, and Naive. The typical classifier of the scikit-learn module included popular machine learning methods including Bayes, Random Forest, and others. A brain tumor is a condition brought on by aberrant brain cell proliferation. Brain tumors can be classified as either benign or malignant, with the former being classified as a cancerous brain tumor. It is difficult to forecast the survival rate of a patient who has a tumor because of the rarity and variety of tumor kinds. Fifteen out of one hundred individuals with brain cancer had a possibility of surviving for ten years or longer after diagnosis, per a UK cancer study. The type of tumor, the location of the tumor in the brain, the abnormalities of the cells, and Additional elements all influence how a patient with a brain tumor is treated.

I. INTRODUCTION

The brain significant organ among the numerous that make up the human body. Brain tumors are among the most frequent causes of brain impairment. All that a tumor is is an overabundance of cells growing out of control. Brain tumor cells proliferate in such a manner that they ultimately absorb all the nutrition intended for the healthy tissues and cells, leading to brain failure. If left undetected, brain tumors can severely impact motor functions, cognition, and even vital physiological processes. At the moment, physicians manually examine the patient's brain MR images to determine the location and extent of the brain tumor. Early and accurate diagnosis is essential to improving patient survival rates and treatment outcomes. Modern imaging technologies and

AI-based tools are increasingly being adopted to reduce human error and assist in faster diagnosis. This is thought to be exceedingly time-consuming and leads to an incorrect tumor detection.[1]




Fig. 1. Brain

The brain consists of a vast number of cells and performs numerous intricate tasks every second. Multiple body functions are impacted by brain injury. Strange. A brain tumor is a growth of tissue in the human brain that impairs the brain's ability to function as best it can. Because it will improve the study's results in an area with ,an extremely little error margin, computer aid is well developed in organizations that provide therapy. Although two-dimensional MRI readings are quite costly, they are of high quality. These days, there is a considerable interest in programming that helps people in therapeutic situations. Human observers highlight the tumor's advantages over conventional methods.[2]

combining (fusing) the pictures obtained from several imaging modalities and taking advantage of new developments in engineering technologies that improve brain tumor detection in computer vision applications, where artificial intelligence (AI) can be combined with these imaging modalities to create computer-aided diagnosis (CAD) systems. These devices can assist doctors in improving the precision of early cancer detection. In order to categorize and identify brain tumors, numerous artificial intelligence approaches have recently been used, including convolutional neural networks (CNN), vector machines for support (SVM), and artificial neural networks (ANN).[3]

A key element of brain tumors and medical imaging detection is necessary for the identification and management of brain-related diseases. Conventional tumor identification methods that involve the manual review of medical images can be laborious and prone to human error. But the rapid advancement Various methods for deep learning, especially in computer vision, has opened up new avenues for the accurate and automated identification of brain cancers in. One kind of profound learning Networks of convolutional neurons (CNNs) are a technology that has been impressive performance in tasks involving image analysis, such as object detection and segmentation. Using deep learning skills, researchers have been examining these techniques for detecting and classifying magnetic resonance imaging (MRI)-identified brain cancers data.[4]

Researchers are putting in a lot of effort to build CNNs that can properly identify and classify brain tumour, as well as other forms of medical imaging, in order to enhance the medical diagnostic and treatment results. With this potential in mind, researchers are working hard to construct CNNs The benefit of deep learning is that it can learn intricate, hierarchical characteristics straight from raw data, eliminating the requirement for explicitly rule-based methods or hand-crafted features. It may have serious health effects implications if not detected and treated early. They can cause a range of symptoms and may lead to neurological disorders or even death.[5]

Image processing has advanced in recent years, proliferated and grown being an essential aspect of the medical industry. Intracerebral neoplasms are another name for brain tumors, which are defined by aberrant cell proliferation in the brain. Two categories exist for these tumors, categories: benign Or malignant. According to visual traits and contrast texture analysis of soft tissue, typical MRI patterns are frequently used to differentiate between various kinds of brain tumors. the WHO, or World Health Organization.[6]

A significant gap in the field of medical imaging and healthcare diagnostics is filled by the study on brain tumor detection utilizing machine learning models. For prompt and accurate clinical therapies, brain tumors must be accurately identified and delineated from medical pictures. Conventional manual segmentation techniques are laborious and prone to inter-observer variation. This research aims to automate and increase the precision of brain tumor segmentation by utilizing cutting-edge deep learning models like U-Net and LinkNet, enabling speedier and more accurate diagnoses. Implementing these models has the potential to enhance treatment planning and patient outcomes Moreover, streamlining healthcare professionals' workflow.[7]

Deep learning is being used in this sector to improve not only the identification of brain tumors but also the categorization and segmentation of tumor kinds, providing

important insights necessary for well-thought-out treatment plans. By utilizing extensive datasets, these AI models can continuously evolve, learning from new data and refining their predictive capabilities over time. Consequently, integrating CNNs into the diagnostic process marks a significant leap forward in neuroimaging, having the capacity to improve patient outcomes through speedier brain tumor diagnosis and precisely. The medulla regulates autonomic processes like breathing and heartbeat Moreover, transmitting messages between the spinal cord and the higher regions of the brain. In fish and amphibians, the primary hub for sensory integration is the midbrain, the upper part of which developed from the optic lobes. It also plays a role in birds' and reptiles' integration. The midbrain is significantly smaller in mammals and mainly acts as a bridge between the forebrain and the hindbrain.[8]

Consequently, it may be presumed that the creation of completely automated computer-aided detection and diagnosis (CAD) systems to help radiologists and clinicians do their jobs more quickly and accurately. Generally speaking, CAD systems for Three phases make up the support for brain tumor classification segmenting the lesion from the image, extracting the tumor's features using statistical or mathematical parameters analysis considering the use of an appropriate machine learning (ML) classifier to forecast the anomaly class . Despite the fact that there are a number of machines learning techniques for classifying MRI brain tumors using the aforementioned method, there is still a significant disadvantage. The traditional method that requires human feature extraction and entails the detection of edges, lines, gradient changes, and intensity-based characteristics.[9]

Classification of adult glioma grades in magnetic resonance imaging will be examined in this thesis study using two CNN models. ResNet50 and VGG-19 are the models that will be utilized for this challenge. The Cancer Genome Atlas (TCGA) dataset will be applied to training the suggested models, which will then be evaluated using a number of assessment measures. The models' capacity to generalize across the various MRI modalities can be evaluated using a variety of performance indicators. As a result, a number of studies have used DL techniques—particularly convolutional neural networks (CNN)—in order to identify brain tumors. Because of the way convolutions operate and the GPU parallelization of convolutive operations, the latter are excellent for image classification jobs and have a quick processing potential.[10]

An organism's brain is the mass of nerve tissue located in its anterior end. In higher vertebrates, the brain serves as the center of learning Furthermore, to integrating sensory data and controlling muscular responses. About 1.4 kg (3 pounds) is the weight of the human brain, and it is composed of neurons, which are billions of cells. Learning, memory, thought creation, and other cognitive processes depend on the transmission of chemical and electrical cues from one neuron

to the next in the brain, which is made possible by synapses, or junctions between neurons. The brains of lower vertebrates are tubular and resemble the brains of higher vertebrates at an early embryonic stage.

II. LITERATURE SURVEY

Using Embodied Conversational Agents (ECAs) as virtual guides, the researchers developed intelligent visitor information points. To organize tourism-related data, these ECAs utilize a unique ontology called TITERIA, developed in the OWL language. This structured knowledge base enables the agents to understand customer inquiries and provide contextually appropriate responses. Furthermore, AI capabilities—such as those offered by the Maxine platform—enhance the ECAs' ability to recommend related areas of interest, thereby improving the user experience. Despite the substantial development expenses related to implementation, the study highlights the potential of integrating AI and semantic frameworks to create intelligent, interactive information systems.[11]

Quantum Variational Classifiers (QVR) in conjunction with ensemble transfer learning was customary for suggest a novel brain tumor detection model. This method involved applying a softmax function to create a score vector after deep features were retrieved using the InceptionV3 architecture. In order to differentiate between four tumor types—pituitary tumor, no tumor, meningioma, and glioma—this vector was subsequently categorized using QVR. Three datasets—BRATS 2020, a local dataset, and Kaggle—were used to test the model, and it produced detection accuracy of above 90

A distinct framework that integrates several explanation techniques, including vanilla gradient, integrated gradients, guided backpropagation, and guided integrated gradients, SmoothGrad, Grad-CAM, and guided Grad-CAM, was created to address the explainability problem in deep learning-based medical diagnosis. By creating visual saliency maps, these techniques improved the interpretability of model choices. In addition to achieving a 98.62% classification accuracy when tested on the BraTS 2019 dataset, our framework increased clinician trust by using a transparent prediction method.[12]

The one that segmentation of brain MRI images from different angles and with various deep learning networks has been investigated in a number of research. Dice scores improved from 0.73 to 0.79 following experimental assessment, indicating that employing multiple segmentation networks generated better performance in comparison to single networks.

A other method suggested using a classification network to separate MR images into groups that are tumorous and those that are not. The classifier was retrained using transfer learning to better identify brain cancers than a number of

current methods.

Furthermore, An analysis of comparisons was conducted. with an emphasis on future research areas, feature extraction, methodology, and classification methodologies. To offer a cohesive perspective and ideas For additional investigation, this study synthesized the advantages and disadvantages of several investigations.

MRI scans were used separately to distinguish between normal and tumorous brain pictures, with a focus on tumor forms such glioblastoma, metastatic bronchogenic carcinoma, and sarcoma. For efficient classification, this technique used wavelet transformations in conjunction with support vector machines (SVM).

In a different research, Convolutions with depth-wise separability were employed. To identify brain tumors using the Xception model. Strong classification performance was achieved by combining this architecture with transfer learning, which substantially decreased the computational cost and model size. The model's potential for computer-aided diagnostics was validated by its excellent prediction accuracy. [13]

Early-stage The identification of Research has been done on brain tumors. using Mathematical Morphological Reconstruction (MMR). This method improves the caliber of medical pictures for further analysis by first pre-processing them to eliminate noise and artifacts. The tumor's benign or malignant status is then ascertained using statistical The textural characteristics that were taken out of the segmented pictures. Additionally, the technique divides pictures into smaller parts, which improves image processing efficiency and accuracy. Studies have shown that this approach successfully detects brain tumors in patients, underscoring its potential for clinical diagnosis. [14]

Numerous research have investigated various image processing methods for MRI scan-based brain tumor identification. One method divided white matter and gray matter in the brain tissues, cerebrospinal fluid, and tumor areas SVMs, or support vector machines, and a biologically inspired Biorthogonal Wavelet Transform (BWT). To get better picture quality, preprocessing methods such as thresholding-based skull stripping were applied to eliminate extraneous features and noise.[15]

Segmentation was highlighted as a critical stage in the detection pipeline in a different survey that compared several methods for processing images in medicine that are employed regarding a brain tumor identification. Preprocessing, feature extraction, classification, and segmentation were all highlighted in a framework that divides tumor detection into these four phases.[16]

The automation of the detection process was identified as an active and developing research subject by other evaluations that looked at current approaches for recognizing and Brain tumor segmentation from MRI pictures. Various entropy functions affected the segmentation output according to their capacity to specify ideal threshold values for differentiating tumor areas, according to some research on entropy-based thresholding strategies.

The diagnosis and grading of brain tumors, especially using MRI imaging, has profited substantially from recent developments in machine learning (ML) and deep learning (DL). One method used deep neural networks (DNN) for classification, principal component analysis (PCA) for dimensionality reduction, and discrete wavelet transform (DWT) in conjunction with fuzzy C-means segmentation. The accuracy and sensitivity of this method were 96.97% and 97.0%, respectively. Using a neural network that is convolutional (CNN) in conjunction with Gray Level Co-occurrence Matrix (GLCM) information that was obtained from many angles, another technique produced an accuracy of 82.27% on particular tumor combinations.[18]

A different DL-based system segmented data using fuzzy C-means, retrieved texture and form features, then categorized the results using SVM and DNN classifiers with an accuracy of 97.5%. Features including intensity histograms, GLCM, and bag-of-words (BoW) were enhanced with approaches like area of interest (ROI) augmentation and fine ring-form partition, which greatly increased classification accuracies for all three methods. The best wavelet-based features were also chosen using genetic algorithms, which reduced dimensionality and achieved 98% accuracy with A network of artificial neurons (ANN) with just four chosen features. The publications described above examine a broad variety of methodologies and approaches for identifying brain tumors. The authors of each study use state-of-the-art technology and evaluation criteria to demonstrate the efficacy of their suggested procedures, despite differences in their methodology. When taken as a whole, these publications significantly advance the current conversation around brain tumor detection. To create more accurate and reliable models for identifying and evaluating brain cancers using magnetic resonance brain images, additional research in this area is crucial.

III. METHODOLOGY

Brain tumors were segmented and identified using a machine learning-based method, and the way that several classifiers was compared. Skull removal, the application of conventional classifiers for segmentation, feature extraction, tumor contouring, segmentation using the Fuzzy C-Means method, and morphological processing are the seven main steps of the suggested brain image segmentation system. All of these actions together increased our method's efficacy. The

following sections provide a comprehensive implementation of the suggested model. [17]




Fig. 2. CNN-based feature extraction and classification model

An MRI brain picture serves as the initial input layer in the convolutional neural network (CNN) architecture. In order to identify low-level patterns like edges and textures, convolutional filters (such as 3x3 kernels) move across the picture. A nonlinear activation function, usually ReLU, is applied after the convolution procedure to provide non-linearity and aid in the network's learning of intricate features. [19]

To draw attention to particular elements of the image, feature maps are created in the convolutional layers. Pooling procedures like max pooling, which decrease spatial dimensions while maintaining crucial characteristics, are then used to downsample these maps. Additionally, this phase reduces computing expense and avoids overfitting.[20]

Higher-level characteristics are extracted by additional convolution and pooling layers as the network gets deeper, capturing intricate structures important for tumor classification. The model is better able to comprehend complex patterns in brain MRI data thanks to these increasingly abstract representations.[21]

A thorough pipeline of preprocessing, segmentation, and deep learning-based classification is used in the brain tumor detection approach. At first, MRI pictures of the brain were

gathered from directories that were arranged according to the many kinds of tumors. Bilateral filtering was used to minimize noise while maintaining crucial edge features, and these photos were scaled to guarantee consistency throughout the dataset. Tumor locations were highlighted using color mapping techniques to improve visibility and speed up preliminary investigation. To identify tumor regions, picture segmentation was done after preprocessing. To make processing easier by lowering the complexity of color channels, each image was first converted to grayscale. Following the use of thresholding, the picture was transformed in a binary format, with the backdrop in black and possible tumor locations indicated in white. To precisely identify and extract the borders of the tumor patches, contour detection was performed on the binary pictures. Ultimately, the segmented and preprocessed pictures were employed to build An in-depth learning paradigm for classifying brain tumors.




Fig. 3. data preprocessing

These show the entire deep learning process for detecting brain tumors. Training, prediction, and data preparation are the three primary phases of the pipeline.

IV. RESULTS AND DISCUSSION




Fig. 4. Accuracy and loss over training epoch

The learning behavior throughout several epochs is depicted in the model training history graph. The Y-axis shows the accuracy and loss values, and the X-axis shows The quantity of training cycles, or epochs. The representation is successfully learning and refining its predictions,As demonstrated by the training accuracy, which rises gradually with each epoch andis depicted by the green line. The training loss, on the other hand, is represented by the red line, which steadily drops over time to show a decrease in prediction error. This general pattern of increasing accuracy and decreasing loss indicates that the model is successfully convergent and represents solid training performance. [22]

1. Data Preprocessing:The first step is MRI image slicing, which involves dividing brain MRI data into several slices in order to identify pertinent brain areas. After that, each slice goes through preprocessing procedures including noise reduction, normalization, and scaling to create standardized, clean input that can be used to train the model.

2. Training Phase: A training dataset is created by dividing the preprocessed slices. Features and patterns are extracted from this data using deep learning models, especially CNN-based architectures like VGG16. The difference between the expected and actual outputs is calculated using a loss function. The model's parameters (weights) are then updated by backpropagation utilizing optimization methods like Adam or SGD. Iteratively, this procedure is carried out until the model performs at its best. [23]

3. Testing and Final Prediction: To assess the training model, a different subset of the preprocessed data is utilized as the test dataset. Based on the learnt features, the top-performing model from the training phase is chosen and used to categorize the input MRI slices in order to determine the kind or existence of brain tumors.




Fig. 5. ROC Curve showing high AUC for all brain tumor classes

We used the Receiver Operating Characteristic (ROC) curve, accuracy, precision, recall, F1-score, and other common classification measures to evaluate the efficacy of the suggested deep learning brain tumor model identification. Four kinds of brain cancers in made up the labeled dataset used to train the model:glioma, meningioma, pituitary, and no tumor.[24]

ROC Curve Analysis:

A popular statistic for evaluating the diagnostic potential of classification algorithms, particularly in the medical imaging, is the ROC curve. The ROC curves for every one of the four tumor classifications are displayed.The following are The Area Beneath the Curve(AUC) values:

- **Class 0 (Glioma):** AUC = 1.00
- **Class 1 (Meningioma):** AUC = 1.00
- **Class 2 (Pituitary):** AUC = 1.00
- **Class 3 (No Tumor):** AUC = 0.99

These findings show that the model performs almost flawlessly in classification, exhibiting incredibly high sensitivity and specificity for every class.

Discussion:

The model's high AUC values indicate that it may effectively differentiate between various brain tumor kinds and healthy patients. Accurate categorization was made possible by the deep learning architecture's successful acquisition of discriminative characteristics from MRI images. Subtle similarities in visual features between healthy and moderately diseased tissue, which are typical in medical imaging tasks, might be the reason for the somewhat lower AUC for the "No Tumor" class (0.99).

While these results are in line with those of other cutting-edge models, they also demonstrate improvements in class-wise AUC and lower rates of misclassification. The model's outstanding performance confirms its potential value in helping neurologists and radiologists identify and categorize brain cancers early on, which would enable prompt and efficient treatment planning.

To verify the model's resilience and generalizability in various contexts, more validation utilizing external datasets and actual clinical trials is required.

By contrasting the predicted labels with the actual ground truth, the confusion matrix offers a clear visual depiction of the model's classification performance. The confusion matrix produced from the test dataset for classifying brain tumors is shown in the figure.




Fig. 6. Confusion Matrix Graph

Confusion Matrix Graph

Interpretation:

- **Rows:** Show the true values for the class labels.

- **Columns:** Represent the predicted class labels (model outputs).
- **Diagonal values:** Indicate correct predictions.
 - 402 *no tumor* images were correctly classified.
 - 279 *glioma*, 288 *pituitary*, and 298 *meningioma* samples were correctly predicted.
- **Off-diagonal values:** Represent misclassifications.
 - 21 glioma cases were misclassified as meningioma.
 - A few pituitary and meningioma cases were confused with one another.

There are very few misclassifications seen overall, according to the confusion matrix, which shows good classification accuracy. The model has a high degree of capacity to differentiate between several types of brain tumors and healthy instances.

V. CONCLUSION

The use of magnetic resonance imaging (MRI) in recent years has emerged as a useful technique for clinical research, with uses including the identification of brain tumors. Using deep learning methods on these MRI pictures aids in finding the tumor. It is evident from the research and application of CNN algorithms that they contribute to the more precise and efficient identification of brain cancers. specific tumor kind and recommend the appropriate course of action. In the future, a range of deep learning algorithms will be required to create a model that will offer tumor location and severity along with quicker, more reliable, and more efficient techniques for early brain tumor categorization and detection.

In this thesis, deep learning was used to classify brain tumor grade using MR data. This was accomplished by classifying three classes using two pre-trained CNN models that used both single MR modalities and combinations of them. VGG-19 was the model that outperformed ResNet50 in the majority of instances on all anatomical planes and had the greatest test accuracy and AUC on the sagittal plane for single MR modalities and their combinations. The Grad-CAMs results suggest that ResNet50 would be a better model from a qualitative standpoint. A brain tumor may be found by looking for a mass of tissue on a patient's MRI image.[?]

This work proposes a the CNN model for classifying brain cancers into tumor-containing and tumor-free groups using MRI data. When compared to existing neural network models, the proposed method for MRI image identification and classification produced the highest accuracy results. Following preprocessing and scaling, The evaluation was conducted using a convolutional neural network. these medical images. Three thousand high-resolution MRI scans were used for training and validation. The effectiveness evaluated using several assessment indicators. The results of the experiment demonstrate that the recommended model outperforms previous CNN models in certain performance

parameters, such as 98% accuracy and 96% overall accuracy.

Because of the sheer quantity of the pictures, image segmentation has a significant part in medical image processing. To differentiate between brain tumors, we employed MRI and CT scan pictures. The most often used use of MRI is the segmentation and categorization of brain tumors. We used fuzzy C-Means clustering, which accurately predicts tumor cells, for tumor segmentation. In this part, conventional classifiers like Support Vector Machi, K-Nearest Neighbor, and others were used and contrasted.

We have researched feature-based work that has already been done within a brain tumor identification. We research image processing methods For example, an image pre-processing, picture segmentation, feature extraction, and classification in feature-based learning. Additionally, research deep learning methods VGG16 and CNN. This method allows us to determine if a tumor is there or not; if it is, the model returns "yes," otherwise it returns "no." CNN and the VGG 16 Model are compared. Comparatively speaking, VGG 16 is more accurate than CNN. Although not all tasks in this sector of development are considered flawless, this application may yet be able to be improved.

This study provides a thorough analysis of the application of deep learning methods to the identification of brain tumors. It emphasizes the vital significance of overcoming the difficulties presented by manual analysis and traditional diagnostic techniques through early detection and accurate diagnosis. There are encouraging prospects to increase brain tumor detection's efficacy and accuracy through the use of machine learning techniques. Numerous machine learning algorithms have been used and examined, such as CNN, SVM, and logistic regression. These algorithms make use of characteristics taken from MRI and other medical imaging data.

REFERENCES

- [1] Naufal Abiwinanda, Muhammad Hanif, Rizky Iqbal, Aurelia Wibowo, and Syafeeza A. R. Abdullah. Brain tumor classification using convolutional neural network. *Procedia Computer Science*, 161:708–715, 2019.
- [2] P. Afshar, A. Mohammadi, and K. N. Plataniotis. Brain tumor type classification via capsule networks. *IEEE International Conference on Image Processing (ICIP)*, pages 3129–3133, 2019.
- [3] Lamiaa A. Ali, Maha M. Salem, and Ashraf E. S. Salama. Brain sectioning tumors and classification applying deep learning techniques. *Journal of International Advanced both computer science and Applications*, 11(12):350–357, 2020.
- [4] Hamza Rafiq Almadhoun and Samy S. Abu Naser. Brain tumor identification through deep learning. *International Journal of Academic Engineering Research (IJAER)*, 6(3):29–47, March 2022.
- [5] Ali Mohammad Alqudah, Hiam Alquraan, Isam Abu Qasmieh, Amin Alqudah, and Wafaa Al-Sharu. Brain classification of tumors through deep learning technique - a comparison between cropped, uncropped, and segmented lesion images with different sizes. *International Journal of Advanced Trends in Computer Science and Engineering*, 8(6):3686–3694, 2019.

- [6] Shtwai Alsubai, Habib Ullah Khan, Abdullah Alqahtani, Mohemmed Sha, Sidra Abbas, and Uzma Ghulam Mohammad. Ensemble using deep learning to identify brain tumors. *Frontiers in Computational Neuroscience*, 16:1005617, 2022.
- [7] Syed Anwar, Md. Mursalin, M. Majid, and M. A. Khan. framework for deep learning in relation to automatic brain tumor classification with mri pictures. *Identifying Patterns Letters*, 129:165–171, 2019.
- [8] Ayushi and Ankit Agarwal. Finding tumors of the brain with deep learning. *Journal of International Scientific Engineering Research*, 11(4):850–854, 2020.
- [9] Jun Cheng, Wei Huang, Shuangliang Cao, Rui Yang, Zhaoxiang Yang, and Xiangyang Ji. Enhanced performance of brain tumor classification via tumor region augmentation and partition. *Pattern Recognition Letters*, 110:67–74, 2018.
- [10] John George and Rahul Sharma. An mri method of deep learning image-based on brain tumors identification. *International Journal of Engineering Research and Technology*, 10(3):147–150, 2021.
- [11] Md Rashedul Islam Hossain, Md. Ashraful Alam, and Mohammad Monirujjaman Khan. Finding brain tumors using convolutional neural networks. *International Journal of Computer Applications*, 180(22):7–11, 2019.
- [12] Aman Jaiswal, Vandana Jaiswal, and Richa Rai. Classification of convolutional neural networks for brain tumors. *Proceedings of the World Intelligent Computing Conference and Control Systems (ICCCS)*, pages 1171–1175, 2019.
- [13] Khawar Masood, Shujhat Khan, and Saba Bashir. Computer-aided diagnosis of brain tumors utilizing mri images: A survey. *Computerized Imaging for Medical Conditions and Graphics*, 45:1–13, 2015.
- [14] Yaser Mohammed, Khaled Baddar, and Amal Alhussien. Brain tumor deep learning-based detection techniques. *International Journal of Advanced both computer science and Applications*, 12(10):167–172, 2021.
- [15] Heba Mohsen, El-Sayed A. El-Dahshan, El-Bakry H. M., and Aboul Ella Hassanien. Classification making use neural networks for deep learning about brain tumors. *Future Computing and Informatics Journal*, 3(1):68–71, 2018.
- [16] Jay Patel and Hiral Shah. Brain tumor detection using cnn and transfer learning. *International Journal of Computer Applications*, 175(29):12–16, 2022.
- [17] Deepa R, Ramya V, and Radhika M. Detection utilizing deep learning for brain tumors technique. *Journal of International Engineering and Technology Research (IRJET)*, 7(5):2246–2251, 2020.
- [18] Thambala Ramesh, Chatragadda Prasanna, Jellapuram Roja, and Tokala Mounika. Deep learning-based brain tumor detection. *International Journal of Food and Nutritional Sciences (IJFANS)*, 10(10):586–590, 2021. UGC CARE Listed (Group-I) Journal.
- [19] S. M. Reza, M. K. Islam, T. Arafat, and M. S. A. Hossain. Brain tumor identification through deep learning. *Worldwide Journal of High-Level Computer Science and Applications*, 9(10):295–299, 2018.
- [20] Muhammad Sajjad, Imran Mehmood, and S. W. Baik. Multi-grade brain tumor classification using deep cnn with extensive data augmentation. *Journal of Computational Science*, 30:174–182, 2019.
- [21] Ahmed M. Sarhan. Automatic classification of mri brain images using deep neural networks using convolutional networks. *Journal of International Advanced Technology and Applications*, 11(3):1–7, 2020.
- [22] Ritika Sharma and R. K. Agrawal. Automated medical diagnosis of brain tumor using deep learning approach. *International Journal of Imaging Systems and Technology*, 30(1):162–175, 2020.
- [23] Zainab J. Swati, U. R. Acharya, P. R. Bhat, E. K. Ng, and J. S. Suri. Brain tumor classification using deep cnn features via transfer learning. *In biology, computers and Medicine*, 103:103–111, 2019.
- [24] Suchetha N. V, Avinash Bhat, Aravind Hegde, Mallikarjun M, and Karthik S. R. Brain tumor detection using a deep learning model. *Sri Dharmasthala Manjunatheshwara Institute of Technology*, 2021. Affiliated to Visvesvaraya Technological University, Belagavi, Karnataka, India.